

Performance Beast

Durable Strength & Conditioning Surfacing

BUILT ON
itsTRU[®]
TECHNOLOGY

PRODUCT ATTRIBUTES

- **2.5mm Vulcanized Composition Rubber (VCR) Surface Layer**
Provides excellent durability and slip resistance
- **8mm Factory Fusion-Bonded VCR Beast Base Layer**
Extremely dense, upcycled VCR minimizes bar bounce and provides ultimate durability

Made using our patented itsTRU[®] technology, Performance Beast is a durable 10.5mm vulcanized composition rubber system that absorbs shock. Designed for heavy strength training, Performance Beast maximizes energy restitution and enhances durability in applications dominated by free weight training



APPLICATIONS

- Selectorized Strength
- Free Weights
- Olympic Style Lifting
- Functional Training
- Cardio

BENEFITS

- Extreme durability
- Sustainable
- Slip-resistant
- Provides substrate protection

NOMINAL DIMENSIONS

Available as a standard in rolls. Talk to your local sales rep to determine availability, pricing, minimums, and lead times.



10.5mm (2.5mm + 8mm) x 48" (1.22m)

NRG[™]




Force Reduction: 11.4%
Absorption of impact energy




Energy Restitution: 72.2%
Useful return of impact energy

Typical Deltec Field Tester Results




Performance Beast


COLOR SWATCHES




Medium Gray ES504




Charcoal ES505




Dark Taupe ES506




Warm Gray ES507




Navy ES508



Green ES509




Maroon ES510



Red ES511




Steel Appeal 2 ES15A




Dark Gray ES502




Mocha Latte 2 ES43A




Blue ES500




Blue Jays ES103




Cardinals ES104




Raiders ES503




Buff Blue 20 ES45




Rippin Red 20 ES47



Grippin Gray 20 ES46



Whey Protein 2 ES97A



Basic Black ES00

TECHNICAL DETAILS

Performance Criteria	Test Standard	Typical Results
Recovery after Static Load	ASTM F970	0.004"
Coefficient of Friction	ASTM D2047	>0.8
FloorScore	CA 01350	Certified
Abrasion Resistance	ASTM D3389	Pass
Flammability - Pill Test	ASTM D2859	Pass
Impact Insulation Class (IIC)*	ASTM E492	55
Delta IIC*	ASTM E2179	24

*Tested on a 6" concrete slab with no ceiling.

