

Performance UltraTile

Rubber Tiles for Ultimate Durability

PRODUCT ATTRIBUTES

- **2.5mm Vulcanized Composition Rubber (VCR) Surface Layer**
Provides excellent durability and slip resistance
- **1" Molded VCR UltraTile Base Layer***
Upcycled VCR molded base layer provides extreme shock absorption and subtrate protection.

*Installed using Ecore's Quad Blok installation system. Quad Bloks allow the flooring system to float and the tiles to be installed in conjunction with RageTurf UltraTiles.

Performance UltraTile® is designed with a patented "ultra" high-density surface layer on a molded base. This 24-by-24-by-1-inch modular tile offers enhanced impact absorption and substrate protection in moderate to extreme weight drop applications.



APPLICATIONS

- Selectorized Strength
- Free Weights
- Cardio
- Olympic Style Lifting
- Functional Training
- Childcare / Playzones
- K-12 / Higher Education
- Outdoor (must be fully adhered)

BENEFITS

- Durable
- Sustainable
- Easy installation with Quad Blok installation system
- Ease of maintenance
- Slip-resistant
- Custom logos available

NOMINAL DIMENSIONS

Available as a standard in 24" x 24" tiles. Talk to your local sales rep to determine availability, pricing, minimums, and lead times.



1" x 24" (61 cm) x 24" (61 cm)



Quad Blok: 1/2" H x 4 3/4" x 4 3/4"

Adhesive = 1 28oz Tube / 40 Quad Bloks

NRG[®]




Force Reduction: 50.2%
Absorption of impact energy



Energy Restitution: 47.9%
Useful return of impact energy

Typical Deltec Field Tester Results



Performance UltraTile

COLOR SWATCHES



Steel Appeal 2 EL15A



Dark Gray EL502



Mocha Latte 2 EL43A




Blue EL500




Blue Jays EL103




Cardinals EL104




Raiders EL503




Gators 3 EL107B




Wildcats 3 EL100B




Vikings EL101




Tigers EL106




Lions EL102




Buff Blue 20 EL45



Rippin Red 20 EL47



Gripping Gray 20 EL46



Whey Protein 2 ES97A



Basic Black ES00

TECHNICAL DETAILS

Performance Criteria	Test Standard	Typical Results
Recovery after Static Load @400 psi	ASTM F970 Modified	0.005"
Coefficient of Friction	ASTM D2047	> 0.8
FloorScore	CA 01350	Certified
Abrasion Resistance	ASTM D3389	Pass
Flammability - Pill Test	ASTM D2859	Pass
Impact Insulation Class (IIC)*	ASTM E492	56
Delta IIC*	ASTM E2179	27

*Tested on a 6" concrete slab with no ceiling.

